

A schematic diagram of a double-rod bellows isolator. It consists of a central bellows tube connected to two rigid end rods. Each end rod is terminated in a mounting bracket. Each bracket features a central circular hole for a bolt and two smaller holes, each with an associated leveling screw for adjusting the bracket's orientation.

652078

â°šă°•ç¼¼	ç°"µç¼¼†
ă°¥ă,š	ă†°ç°°è½¼!
èš°-æ°°	2
ç°"µăž:	24
éč°•ă@šç°"µæµ•	500.0
æ †ă††	STANAG 4074
æ°•ă°'èçžæž¥æ°°é†°	2
è®¼è®¼/ç°°~æœ°	ă°-æ²¹
ă°šè°«æ°•æ-™	é²æš°é†°ă±ž
ă°šè°«éčœè°°²	é»'è°°²
ç«°-ç°-ç°°~æœ°	æç°°é°°®ă,½
ç«°-ç°-æ°•æ-™	æç°°èf¶
ç«°-ç°-éčœè°°²	é»'è°°²
æž¥èš æ°•éčœè°°²	é»'è°°²
æž¥èš ç°°~æœ°	æž¥èš é°
æž¥èš èj°é°č	é¶¶¼°Ag¶¼°°°
æž¥èš ¶¼šéč,ç°°°ă°žæœčă°šæ°°é°čé°čçš°¶¼°mm²¶¼°ă°°¼ç°°ç	70.0
ç°"µç¼¼†ç°°çé°çă°¶¼°ç±¶¼°°°	15.0
ç°"µç¼¼†ç°°çé°çă°¶¼°èç±ă°¶¼°°°	600.0
ç®ççŸ°-æ°•èç°°	n.a.
Berechnete_Produktbezeichnung	2P/24V(500A) ç°"µç¼¼†ç°°ç (STANAG 4074)
KEYWORDS	2P,24V,500A,Leitung,STANAG 4074,652078